

### BEST PRACTICES NOTES:



DRAIN PIPE RAISED TO ACCOMODATE OUTLETS THROUGH THE WALL FACE (CHAPTER 4.1)




LOW PERMEABILITY GRANULAR SOILS SHOULD BE PLACED TO CREATE A SHELF INSIDE THE MASS (CHAPTER 4.1)




1 ft<sup>3</sup>/ft (0.3 m<sup>3</sup>/m) OF ADDITIONAL WALL ROCK SHOULD BE PLACED AROUND HEEL DRAIN WHEN INFILL MATERIAL USED IS FINE GRAINED COHESIVE SOILS HAVING A PLASTICITY INDEX (PI) OF > 6 & LL > 30 (CHAPTER 4.2)

\* REFER TO BEST PRACTICE TYPICAL ALLAN BLOCK DRAWING 1.0 FOR REINFORCED WALL APPLICATIONS AND ALL OTHER NOTES, DETAILS AND SPECIFICATIONS.

\* SEE BEST PRACTICES DOCUMENT CHAPTER 4.0 FOR MORE ALTERNATIVE DRAIN NOTES



Designed By: KAH	Title: <b>BEST PRACTICES WATER MANAGEMENT - ALT. DRAIN</b>	Date: 07/17/2019
Checked By: RJL	 This drawing should not be used for final design or construction without the certification of a professional engineer registered in the state in which the wall will be built. The accuracy and use of details contained in this document are the sole responsibility of the user. The user must verify each detail for accuracy as they pertain to their particular project. © 2005 Allan Block	Project No: N/A
Scale: NOT TO SCALE		Drawing No: N/A